

Signature Series

Revolutionize your Workflow with the Transducerized **SPT Series**

SPT Series Transducerized Cordless Tools enable unrestricted mobility throughout assembly while providing precise delivery of torque & angle to the fastener



PRECISE MEASUREMENT

Built-in transducer means accurate measurement and torque delivery



ULTIMATE FLEXIBILITY

Three selectable tightening strategies:

- Torque Control
- Torque Control with Angle Monitoring
- Angle Control



IMMEDIATE FEEDBACK

LED indicator provides simple process information to the operator. Signal is visible from any angle



EASY PROGRAMMING

Program tool via built-in digital interface or UI software. Easily change preset values and strategies, and access stored information



DURABLE CONSTRUCTION

High-strength steel gearing for durability



Signature Series

CORPORATE HEADQUARTERS
10000 SE Pine Street
Portland, Oregon 97216
Phone: (503) 254-6600
Toll Free: 1-800-852-1368

AIMCO CORPORATION DE MEXICO SA DE CV
Ave. Cristobal Colon 14529
Chihuahua, Chihuahua. 31125
Mexico
Phone: (01-614) 380-1010

SPT Transducerized Cordless Tools: Mobility and Precision for Maximum Productivity

The Signature Series SPT Cordless Tools add a reliable efficiency to the assembly process while confirming quality. These easy-to-use, portable tools are transducerized so torque delivery and measurement is precise and traceable. Programmable through either the tool interface or UI software, and available in two model configurations, the SPT tool series is flexible enough to meet your application requirements.

FEATURES AND BENEFITS

- Transducer control for precise torque measurement and traceable results
- Durable high-strength steel gearing means less downtime and lower cost of ownership
- Easy programming on back of tool. Programming interface displays realtime Torque/Angle
- LED indicator lights provide immediate feedback to the operator. The signal is visible from any angle
- Forward/Reverse press button for easy operation
- LED work light for working in dark areas
- Mini USB Port (MUST be used with SPT-USBD) for programming tool with UI Software
- Variable speed control trigger is a non-contact switch, which means longer trigger life
- Optional WiFi communication
- Li-Ion battery pack delivers longer run time
- Shock absorbing, ergonomic grip means less fatigue and well-balanced operation
- When paired with the optional DWL-B receiver, Poka-Yoke connection to Line Controls is easy



Available in pistol and angle configurations.
Fully customizable head options



SPT Signature Series Transducerized Cordless Tools

Model	Torque Range		Free Speed	Battery		Weight		Noise Level
	NM	FT-LB	RPM	(V)	LB	KG	Anvil Size	dB(A)
Pistol Tools* Q = Quick Change Output								
SPT-P825Q	3 - 8	2.2 - 5.9	220 - 1,100	20	2.23	1.01	1/4" QC	<75
SPT-P825	3 - 8	2.2 - 5.9	220 - 1,100	20	2.23	1.01	1/4" Sq Dr	<75
SPT-P1225Q	4 - 12	3 - 8.9	150 - 700	20	2.23	1.01	1/4" QC	<75
SPT-P1238	4 - 12	3 - 8.9	150 - 700	20	2.23	1.01	3/8" Sq Dr	<75
SPT-P1625Q	5 - 16	3.7 - 11.8	100 - 500	20	2.23	1.01	1/4" QC	<75
SPT-P1638	5 - 16	3.7 - 11.8	100 - 500	20	2.23	1.01	3/8" Sq Dr	<75
Angle Tools** Q = Quick Change Output								
SPT-A1025Q	4 - 10	3 - 7.4	150 - 750	20	3.7	1.68	1/4" QC	<75
SPT-A1038	4 - 10	3 - 7.4	150 - 750	20	3.7	1.68	3/8" Sq Dr	<75
SPT-A1625Q	5 - 16	3.7 - 11.8	120 - 600	20	3.7	1.68	1/4" QC	<75
SPT-A1638	5 - 16	3.7 - 11.8	120 - 600	20	3.7	1.68	3/8" Sq Dr	<75
SPT-A3038	10 - 30	7.4 - 22	70 - 350	20	3.7	1.68	3/8" Sq Dr	<75
SPT-A4838	20 - 48	14.8 - 35.4	60 - 210	20	4.77	2.16	3/8" Sq Dr	<75
SPT-A4850	20 - 48	14.8 - 35.4	60 - 210	20	4.77	2.16	1/2" Sq Dr	<75
SPT-A6038	25 - 60	18.4 - 44.3	50 - 170	20	4.77	2.16	3/8" Sq Dr	<75
SPT-A6050	25 - 60	18.4 - 44.3	50 - 170	20	4.77	2.16	1/2" Sq Dr	<75

* Pistol Tools Include: Tool and one (1) 20V Li-Ion Battery

** Angle Nutrunners include: Head Indexing Spanner Wrench and one (1) 20V Li-Ion Battery

BATTERIES, CHARGER, AND RECEIVER FOR SPT TOOLS



Battery Model	Voltage	Type	Capacity	Weight
SPB-2025	20V	Li-Ion	2.5 Ah	.9 Lb/.4 kg
SPB-2025HC	20V	Li-Ion	5.0 Ah	1.5 Lb/.67 kg

Charger Model	Output	Input	Dimensions (W/O Battery)	Weight
SPC-C218-20	18V-19.2V 3.0 A	100-240VAC 50-60 Hz	6.25" (D) x 5" (W) x 3.5" (H) 158.8 mm x 127 mm x 89 mm	1.2 Lb .54 kg

Receiver Model	Input	Ports
DWL-B	100-240VAC 50-60 Hz	25 Pin Parallel and 9 Pin Serial

