



















DOCUMENT CONTROL	
PRINTED COPIES OF THIS DOCUMENT ARE CONSIDERED TO BE UNCONTROLLED DOCUMENTS. HOLDERS ARE RESPONSIBLE FOR ZERIFYING THE CURRENT REVISION LEVEL WITH PURCHASING OR PRIGHTER TO USE OR FABRICATION. THE CONTROLLED VERSION OF THIS DOCUMENT IS FIED FOR TRONLED IN MAINTAINFE	
PROPRIETARY AND CONFIDENTIAL	
THIS DRAWING CONTAINS INFORMATION STRICTLY CONFIDENTIAL TO ACRADYNE/AIMCO, IN THE ABSENCE OF EVENESSES MIGHTEN DEPMISSION ACRADALE/AIMCO	

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING CONTAINS INFORMATION STRICTLY CONPIDENTIAL TO ACREADYNEAMING. IN THE ABSENCE OF EXPRESSED WRITTEN PERMISSION, ACRADYNE/AMICO HAS LOANED THIS COPY WITH THE MUTHAL UNDERSTANDING THAT (A) IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAT (A) IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAT (A) THAT HAS THE DESCRIPTION OF THE CONTAINED HEREIN WILL NOT BE DISCLOSED IT OTHERS.
CONTAINED HEREIN WILL NOT BE DISCLOSED TO OTHERS, (C) IT WILL NOT BE REPRODUCED, AND (D) IT WILL BE RETURNE TO ACRADYNE/AIMCO IMMEDIATELY UPON DEMAND.

	REVISION BLOCK					ACRA
RS, IRNED	REVISION LEVEL	REVISION RELEASE DATE	DESCRIPTION OF CHANGES MADE TO PART	ECN#	AUTHOR/ APPROVAL	DRAW
E CO DING ER ATA RS,						.X = ±.0 REMO
TO BE LE FOR NG OR OLLED INED.						DIME

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES IMENSIONS AND TOLERANCING PER ANSI Y14.5 SURFACE ROUGHNESS PER ANSI Y14.36

BLOCK TOLERANCING PER DECIMAL: ±.030 .XX = ±.010 .XXX = ±.005 .XXXX = ±.0005 ANGLE = ±0°30'

MOVE BURRS AND SHARP EDGES: R.015 MAX ACHINE SURFACE FINISH: 125 RMS OR BETTER

CONTROLLER ASM. W/TOUCHSCREEN & I/O, TOP EXIT

OLIV 4				
AWING	NUMBE			

PART / DRA iEC4EGV\_-T AWINGS AND TECHNICAL DOCUMENTS CONTROLLED BY:
RADYNE MECHANICAL ENGINEERING

D ILC4EGV\_-1

SCALE 1:4 DO NOT SCALE DRAWING SHEET 2 OF 2

REVISION